

QUICK TIPS

- Do not thin or mix with any other products or use as an additive to paint.
- Do not apply Ready Seal over painted or newly stained surfaces. Sealed surfaces inhibit penetration.
- Do not apply Ready Seal on grey, weathered wood. The wood must be cleaned before applying Ready Seal.
- Ready Seal is darkest when first applied. It reaches its true colour in approximately 14 days.
- Colour will vary depending on the type of wood.
- Dispose of in accordance with local, provincial and federal law.
- Ready Seal contains no linseed oil and will not stain hands.
- Ready Seal is biodegradable when in contact with soil and water.



APPROXIMATE COVERAGE

SPRUCE FENCE	14 m ² /L (150 ft ² /gal)	PINE FENCE	14 m ² /L (150 ft ² /gal)
CEDAR FENCE	12 m ² /L (125 ft ² /gal)	TREATED PINE DECK	14 m ² /L (150 ft ² /gal)
TREATED PINE DECK (OLD)	14 m ² /L (150 ft ² /gal)	TREATED PINE DECK (NEW)	14 m ² /L (150 ft ² /gal)
CEDAR DECK	14 m ² /L (150 ft ² /gal)	CEDAR SIDING (SMOOTH)	14 m ² /L (150 ft ² /gal)
CEDAR SIDING (ROUGH)	12 m ² /L (125 ft ² /gal)	PINE SIDING	16 m ² /L (170 ft ² /gal)
CEDAR SHINGLES	14 m ² /L (150 ft ² /gal)	REDWOOD DECK	16.25 m ² /L (175 ft ² /gal)

Note: Actual coverage will vary due to surface porosity, texture and condition of wood.

IMPORTANT INFORMATION

EMERGENCY RESPONSE # (chemtrec)

1-800-424-9300

KEEP OUT OF REACH OF CHILDREN

VOC: less than 100 g/L

READYSEAL.COM

403575 0126



READY SEAL™

EXTERIOR PENETRATING WOOD STAIN & SEALER



**Goof
Proof™**

✓ **NO LAPS. NO RUNS.
NO STREAKS.™**

✓ **NO BACK BRUSHING**

THE PRODUCT OF CHOICE BY THE PROFESSIONALS™



WHAT IS READY SEAL?

Ready Seal is an oil-based, semi-transparent sealer and stain in one. It is a unique blend of resin, pigment, oil, and algaecide that penetrates deeply into wood to protect and preserve it from the elements. Ready Seal can be used on all types of wood. Ready Seal contains trans-oxide pigments that provide superior UV protection.

The trans-oxide pigments help protect wood from fading and greying. Darker colours provide more UV protection. To properly maintain wood, a light cleaning and re-coat are recommended every 2 years on horizontal surfaces and every 3 to 4 years on vertical surfaces. Variances in the product longevity may be caused by original surface condition, application of product, and geographic location. Ready Seal is intended for exterior wood surfaces only.



SURFACE PREPARATION

- Surface must be clean of mildew, dust, dirt, oil and grease. Remove any mildew stains with Moldex® Mould and Mildew Stain Remover or by washing the surface with a solution of one cup household bleach in a 3.78 L (1 gallon) of water.
- All other stains must be completely removed by stripping.
- Caustic strippers must be neutralized thoroughly with water.
- Before staining, wood must dry completely. Allow 48 to 72 hours depending on weather conditions.
- Protect against overspray and cover all plants and vegetation with drop cloth before applying Ready Seal.

APPLICATION INSTRUCTIONS

- Before treating wood, test in a small inconspicuous area to ensure satisfaction with appearance.
- Use a brush, roller or pump-up sprayer to apply Ready Seal.
- Blend multiple containers together to ensure colour consistency.
- Apply two light coats of Ready Seal to wood surface. Allow at least 45 minutes between coats.
- Allow 48 to 72 hours of drying. Drying time will vary depending on temperature, humidity and surface porosity.

CLEAN-UP

- Clean equipment immediately with paint thinner or mineral spirits.
- Dispose empty containers, unused or unwanted product in accordance with local, provincial and federal law.