

TECHNICAL DATA – CHALKBOARD PAINT

DESCRIPTION: A fast dry solvent based flat paint, suitable for use on wood, metal, Masonite, drywall, plaster and more.

RECOMMENDED USES: Provides a writeable, erasable finish that is decorative and functional, where a durable flat finish is required.

COLORS/FINISH: Black or Green/Flat finish

APPLICATION: Easily applied with a brush or roller. A brush suitable for oil-based paints and a short nap roller are recommended. Maintain a wet edge during application. Do not overbrush.

THINNING & CLEAN UP: No thinning should be required for roller or brush application. Clean up using xylene or toluene immediately following application.

SURFACE PREPARATION: All surfaces must be free from contamination, oil, and grease. High gloss surfaces should be lightly sanded to ensure good adhesion. Primers used must be compatible with strong solvents.

COVERAGE: Coverage is approximately 90 square ft. per quart.

DRY TIME: The coating will dry tack free in about 1 hour and may be re coated after two hours. Allow 24 hours drying, before washing.

SAFETY INFORMATION: Product is flammable. Keep away from heat and open flame and do not use in confined areas. Ensure adequate ventilation is present at all times.

Keep containers tightly sealed for storage. Dispose of empty container as hazardous waste.

Shelf life 18 months in an unopened container.

Rev. March 24, 2020