

Distributions Fillion Marquis International Itée 420 Industriel Blvd., local 100, Saint-Jean-sur-Richelieu, QC J3B 4S6 Tel.: 450-349-2226 • Fax: 450-349-1799 • Toll free: 1-877-989-2226

passeportelite.com

TECHNICAL SHEET DRY TIME EXTENDER PE700368 • PE700369

DESCRIPTION

Packaging: PE700368 - 236 ml PE700369 - 946 ml

Passeport Élite Dry Time Extender for Water-Based Paints and Varnishes is a high-quality product that lengthens the drying process, making application easier.

It keeps the surface wet for longer, improves flow and levelling, and prevents brush and roller marks. This product is particularly useful in high temperatures or low relative humidity.

PRODUCT SPECIFICATIONS

Appearance	Colourless and odourless liquid
Density	1,034 kg/L
Boiling point	188°C (370 °F)
Flash point	99°C (210 °F) (closed cup)
Solubility in water	Soluble
VOC	100 %
Shelf life	At least 1 year in a well closed container.

DIRECTIONS FOR USE

Mix the product well before adding the extender.

Stir while adding the recommended amount of extender into the paint or varnish. Let stand for 15 minutes before applying the product.

Passeport Élite Water-Based Varnish & Passeport Élite Hybrid Varnish: Maximum 2% of extender. An excess of extender will affect the hardness and resistance of the varnish. Water-Based paints: Add 2-6% of extender.

CAUTION: The addition of extender slows the varnish hardening process; your varnish will require a longer cure time before sanding and applying a second coat.

RESTRICTIONS

STORAGE: Store in a cool, well-ventilated area. FREEZE-THAW STABLE. KEEP OUT OF REACH OF CHILDREN.

LIMITATION OF WARRANTY

The manufacturer's liability, expressed or implied, is limited to the replacement of the product. The user assumes full responsibility for use in accordance with the product data sheet. The manufacture is not liable for any direct, indirect, consequential, economic or other damages.



TECHNICAL SHEET DRY TIME EXTENDER PE700368 • PE700369