

Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199

SECTION 1.	IDENTIFICATION	
	Product identifier	Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199
	Other Means of Identification	N.A.
	Recommended Use	Low viscosity Epoxy Coating
	Restrictions on Use	Unknown
	Supplier Identifier	SCI COATINGS INC. 8320 Rue Grenache, Anjou, Québec Canada H1J 1C5 www.scicoatings.com
	Emergency Phone No.	Numéro d'urgence 24 heures au Canada (CANUTEC): (613) 996-6666
SECTION 2.	HAZARD IDENTIFICATION	
	Classification Acute Toxicity, Oral (Category 4) Acute Toxicity, Dermal (Category 5) Skin Sensitization (Category 1A) Skin Corrosion/irritation (Category Serious eye damage/irritation (Cate Reproductive toxicity (Category 2) Hazardous to the aquatic environm Hazardous to the aquatic environm Label Elements	1B) egory 1) nent - acute (Category 1)



Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199

Signal Word

Danger

Hazard Statements

H302 Harmful if swallowed

H312 Harmful in contact with skin

H317 May cause an allergic skin reaction

H314 Causes severe skin burns and eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H360 May cause harm to breast-fed children

H361 May damage the unborn child. Suspected of damaging fertility

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.

P263 Avoid contact during pregnancy/while nursing.

P264 Wash with plenty of water and soap thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P341 + P311 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P362 + P364 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use water spray, dry powder, or foam for extinction.

P233 Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards:

Unknown

GHS Special Labeling:

EUH205 - "Contains epoxy constituents. May produce a skin allergy."



Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199

SECTION 3.	COMPOSITION					
	Chemical Name	CAS No.	EC No.	% concentration		
	Epoxy adduct	Proprietary	216-823-5	10-30%		
	Isophorone diamine	2855-13-2	220-666-8	10-30%		
	Benzyl alcohol	100-51-6	202-859-9	1-10%		
	4-nonylphenol, branched	84852-15-3	284-325-5	10-30%		
	Polyoxypropylene diamine	9046-10-0	937-402-9	20-40%		
	Inhalation: IF INHALED: Remove person to fresh air and kerst Skin Contact: Flush with soap and water for a minimum of 15 Eye Contact: Rinse immediately with plenty of water for at lead ingestion: Rinse mouth and then drink plenty of water. Do the victim is unconscious or having convulsions Most Important Symptoms and Effects, Acute Burning pain and severe corrosive skin damage burns to the respiratory tract. May cause an alle include stinging, tearing, redness, swelling, and result. Immediate Medical Attention and Special Tree Provide general supportive measures and treat flushing, remove clothes which do not adhere to to hospital. Keep victim warm. Keep victim under	minutes. Consult a physi ast 15 minutes. Consult a not induce vomiting. New . Immediate medical atte e and Delayed a. Can burn mouth, throat gic respiratory reaction. blurred vision. Permaner eatment: symptomatically. Chemic o affected area. Call an a	cian if irritation p physician. /er induce vomiti ntion required. :, and stomach. (Causes serious nt eye damage in cal burns: Flush (mbulance. Conti	ng or give anything by mouth Can cause severe irritation an eye damage. Symptoms may ncluding blindness could with water immediately. While nue flushing during transport		



Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199

SECTION 5.	FIRE-FIGHTING MEASURES
	<u>Extinguishing Media</u> Suitable Extinguishing Media In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2). Unsuitable Extinguishing Media Water jet
	Specific Hazards Arising from the Product During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.
	Special Protective Equipment and Precautions for Fire-fighters Self-contained breathing apparatus and turn-out gear must be worn in case of fire.
SECTION 6.	ACCIDENTAL RELEASE MEASURES Personal Precautions, Protective Equipment, and Emergency Procedures Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment. Methods and Materials for Containment and Clean up For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.
SECTION 7.	HANDLING AND STORAGE
	Precautions for Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or mist. Do not get in eyes, on skin, or on clothing. Do not get this material in contact with eyes. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Keep away from sources of ignition -No smoking. Take precautionary measures against static discharge.
	Conditions for Safe Storage Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.



Safety Data Sheet (SDS) Passeport Elite Industrial High Solid Low-Viscosity **Epoxy Coating Clear - Part B** PE700199

	EXPOSURE CONTROLS / PERSONAL PROTECTION						
	Control Parameters						
	All protective clothing should be appropriately clean and available to dress into before work. The engineering measu or controls and PPE recommendations are only guidelines and may not apply to every situation. Data not available. additional information, please consult the corresponding requirements under						
	http://www.ccohs.ca/topics/hazards/chemical/chemicals/						
		ACGIH® TLV®	OSHA PEL	AIHA®	WEEL®		
С	Chemical name	TWA STEL©	TWA Ceiling	8-hr TWA	Short-Term		
A	ppropriate Engineering Control	<u>s</u>					
	ocal exhaust ventilation required.						
	local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible						
	xposure limit. Emergency eye was						
In	mmediate vicinity of any potential e	exposure. Ensure all	national / local reg	ulations are of	served.		
) Ir	ndividual Protection Measures						
	General Measures						
	o not eat, drink or smoke during w						
	o not allow out of the workplace. C	Clean hands and any	exposed skin thore	oughly after wo	ork and before breaks.		
	Eye / Face Protection Ise tightly sealed goggles or safety	, alassas with side sl	aiolde which are re	sistant to Chor	micale		
	Skin Protection	y glasses with side si	lielus which are re		IIICais.		
-	Vear chemical resistant protection	gloves. Wear imperv	vious clothing as ne	ecessary to pro	otect against coming in co		
	vith product.		C C				
) IR	Respiratory Protection						
	insufficient ventilation, wear respi	ratory protection.					
		ratory protection.					
lf							
lf P	insufficient ventilation, wear respi		Clear Liquid				
lf P A	insufficient ventilation, wear respi		Clear Liquid Not available				
lf P A O	insufficient ventilation, wear respi						
lf P A O O	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor		Not available				
lf A O O P	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor Ddor threshold		Not available Not available				
lf A O O P M	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Oppearance Odor Odor threshold		Not available Not available Not available				
If A O O P M Ir	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Oppearance Odor Odor threshold H Melting point		Not available Not available Not available Not available				
If A O O P M Ir F	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor Odor threshold H Melting point nitial Boiling Point / Range		Not available Not available Not available Not available Not available				
If A O O P M Ir F E	Insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Oppearance Odor Odor threshold H Melting point Initial Boiling Point / Range Iash point Vaporation rate		Not available Not available Not available Not available Not available >93°C Not available				
If А О О Р М I: F Ш F	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor Dodor threshold H Melting point hitial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas)		Not available Not available Not available Not available Not available >93°C Not available Not available				
	HYSICAL AND CHEMICAL PRO Provide the second		Not available Not available Not available Not available Not available >93°C Not available Not available Not available				
If A O O P M Ir F E F L U	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor Dodor threshold H Melting point Initial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas) Lower flammable/explosive limit Ipper flammable/explosive limit		Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available				
	HYSICAL AND CHEMICAL PRO Provide the second		Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available				
	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Odor Dodor threshold H Melting point Initial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas) Lower flammable/explosive limit Upper flammable/explosive limit Yapor pressure Yapor density		Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available Not available				
If P A O O P M IF H F L O V V S	HYSICAL AND CHEMICAL PRO Person Present Content of the second sec		Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available Not available Not available				
	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Ddor Ddor threshold H Melting point itial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas) Lower flammable/explosive limit Vapor pressure Vapor density Specific gravity Solubility	PERTIES	Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available Not available Not available 0.9 - 1.0 Partial				
「 「 「 「 「 「 「 「 」 「 」 「 」 「 「 」 「 「 」 「 」 「 「 」 「 」 「 」 () ()) ()) ())))) ())))	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Door Door threshold H Melting point nitial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas) ower flammable/explosive limit Ipper flammable/explosive limit /apor pressure /apor density specific gravity Solubility Partition coefficient-n-Octanol/wa	PERTIES	Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available Not available O.9 - 1.0 Partial Not available				
If Р A O O P M IF H L J V V S S P A	insufficient ventilation, wear respi PHYSICAL AND CHEMICAL PRO Appearance Ddor Ddor threshold H Melting point itial Boiling Point / Range Tash point Evaporation rate Tammability (solid; gas) Lower flammable/explosive limit Vapor pressure Vapor density Specific gravity Solubility	PERTIES	Not available Not available Not available Not available Not available >93°C Not available Not available Not available Not available Not available Not available Not available 0.9 - 1.0 Partial				

April 09, 2024 Revision #1



Safety Data Sheet (SDS) Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B

PE700199

SECTION 10.	STABILITY AND REACTIVITY			
	Reactivity	Non-reactive		
	Chemical stability	Stable under recommended handling and storage conditions		
	Possibility of Hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.		
	Conditions to avoid	Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions.		
	Incompatible materials	Strong oxidizing agents and acids.		
	Hazardous decomposition products	Unknown		
ECTION 11.	TOXICOLOGY INFORMATION			
	Likely Routes of Administration	Inhalation, skin contact, eye contact, ingestion.		
	Acute Toxicity	Oral: Phenol LD50: 317 mg/kg (rat) Dermal: Harmful in contact with skin LD50: 850 mg/kg		
	LD50 and LC50 Data	Not available		
	Skin Corrosion/Irritation	Causes skin irritation.		
	Serious Eye Damage/ Irritation	Causes serious eye damage		
	STOT (Specific Target Organ Toxicity) Single Exposure Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
	Aspiration Hazard	Not classified based on available data.		
	STOT(Specific Target Organ Toxicity) Repeated Exposure	Skin, eyes, central nervous system, respiratory system		
	Respiratory and/or Skin Sensitization	No data		
	Carcinogenicity Chemical name	Unknown IARC ACGIH® NTP OSHA		
	Reproductive Toxicity	Not available		
	Germ Cell Mutagenicity	Not available		
	Interactive Effects	Not available		
ECTION 12.	ECOLOGICAL INFORMATION Toxic to aquatic life with lasting effects. This is not required by WHMIS. This is not required by OSHA HCS 2012.			
ECTION 13.	DISPOSAL CONSIDERATIONS Disposal Methods Dispose of contents/container into safe container	in accordance with local, regional or national regulations.		



Safety Data Sheet (SDS) Passeport Elite Industrial High Solid Low-Viscosity

Epoxy Coating Clear - Part B PE700199

SECTION 14.	TRANSPORT INFORMATION UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations: UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III				
	UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime): UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT				
	<u>UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):</u> UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT				
SECTION 15.	REGULATORY INFORMATION Complies with regulation (EC) n°1907/2006 Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).				



Safety Data Sheet (SDS) Passeport Elite Industrial High Solid Low-Viscosity Epoxy Coating Clear - Part B PE700199

SECTION 16.

OTHER INFORMATION	
Date of Preparation	August 2022
Date of Last Revision	April 09, 2024
Revision Indicators	The entire MDSD was changed in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces. (REACH), Annex 11, amended by Regulation (EU) No 2020/878-France.
References	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s)
ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

NOTICE: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Passeport Élite will not be liable for any damages resulting from its use since Passeport Élite cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.