


| SECTION 1. IDENTIFICATION | |
|--------------------------------------|---|
| Product identifier | Industrial Epoxy - Comp. A CLEAR |
| Other Means of Identification | PE700231 |
| Recommended Use | Epoxy Resin – Vapor reduction membrane |
| Restrictions on Use | Unknown |
| Supplier Identifier | SEALCHEM INDUSTRIES INC. 2821 Boul. Le Corbusier Laval, Quebec Canada H7L 4J5 Web: www.sealchem.com |
| Emergency Phone No. | 24-Hour Emergency Telephone Number Canada (CANUTEC) : (613) 996-6666 |

| SECTION 2. HAZARD IDENTIFICATION | |
|---|--|
| Classification | Skin Sensitization Category 1B Skin Corrosion/irritation Category 2 Serious eye damage/irritation Category 2A Acute Toxicity, Oral Category 5 Hazardous to the aquatic environment - acute Category 2 Hazardous to the aquatic environment - chronic Category 2 |
| Label Elements | |
|  | |
| Signal Word | Warning |
| Hazard Statements | |
| H303: May be harmful if swallowed | |
| H315: Causes skin irritation | |
| H317: May cause an allergic skin reaction | |
| H319: Causes serious eye irritation | |
| H401: Toxic to aquatic life | |
| H411: Toxic to aquatic life with long lasting effects | |
| Precautionary statements | |
| Prevention: | |
| P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash with plenty of water and soap thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/eye protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P337 + | |

P313 If eye irritation persists: Get medical advice/attention. P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P312 IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell. P362 + P364 Take off contaminated clothing and wash before reuse. P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

| Chemical Name | CAS No. | % concentration |
|--|------------|-----------------|
| Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin | 25085-99-8 | 60 - 100 % |
| alkyl glycidyl ether | 68609-97-2 | 1 - 10 % |
| benzyl alcohol | 100-51-6 | 1 - 10 % |

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Ingestion:

IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this might spread the fire.

Specific Hazards Arising from the Product

During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

Special Protective Equipment and Precautions for Fire-fighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire-fighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---------------|
| Appearance | Clear Liquid |
| Odor | Odorless |
| Odor threshold | Not available |
| pH | Not available |
| Melting Point | Not available |
| Initial Boiling Point / Range | Not Available |
| Flash point | >93 |
| Evaporation rate | Not available |
| Flammability(solid; gas) | Not available |
| Lower flammable/explosive limit | Not available |
| Upper flammable/explosive limit | Not available |
| Vapor pressure | Not available |
| Vapor density | Not available |
| Specific gravity | 1.14 |
| Solubility | Partial |
| Partition coefficient – n- Octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---------------------------|--|
| Reactivity | Non-reactive |
| Chemical stability | Stable under recommended handling and storage conditions |

| | |
|---|---|
| Possibility of Hazardous reactions | This product will polymerize if mixed with an amine. Considerable heat can evolve. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Avoid unintended contact with amines. |
| Incompatible materials | Strong oxidizers, strong alkalis, strong mineral acids, amines. |
| Hazardous decomposition products | Unknown |

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/ Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation

No data

Aspiration Hazard

Not classified based on available data.

STOT(Specific Target Organ Toxicity) – Repeated Exposure

No data

Respiratory and/or Skin Sensitization

May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema.

Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination

Carcinogenicity

Unknown

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Hazardous to aquatic environment
 Persistence and degradability: Not enough data available.
 Bio accumulative potential: Bioconcentration potential is moderate.
 Mobility in soil: Low potential for mobility in soil.
 Other adverse effects: No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

SECTION 15. REGULATORY INFORMATION

Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).
Environmental Canadian regulations specifics: Refer to section 3 for ingredient(s) of the DSL.

SECTION 16. OTHER INFORMATION

| | |
|--|--|
| Date of Preparation | August 2020 |
| Date of Last Revision | June 1, 2014 |
| Revision Indicators | The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces. |
| References | 1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s) |
| ACGIH ATE CAS DSL IARC IATA | American Conference of Governmental Industrial Hygienists Acute toxicity estimate Chemical Abstract Service Domestic Substance List International Agency for Research on Cancer International Air Transport Association |

SAFETY DATA SHEET (SDS)
Industrial Epoxy - Comp. A CLEAR
PE700231

Date and version: November 14, 2022, Version 1

| | |
|-------|--|
| IMDG | International Maritime Dangerous Goods Code |
| LC | Lethal concentration |
| LD | Lethal Dosage |
| NIOSH | National Institute for Occupational Safety and Health |
| NTP | National Toxicology Program (U.S.A.) |
| OSHA | Occupational Safety and Health Administration (U.S.A.) |
| PEL | Permissible Exposure Limit |
| STEL | Short-term Exposure Limit |
| TDG | Transport of dangerous goods in Canada |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| TWA | Time Weighted Average |
| WHMIS | Workplace Hazardous Materials Information System |

Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that SCI Coatings Inc will not be liable for any damages resulting from its use since SCI Coatings Inc cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

| SECTION 1. IDENTIFICATION | |
|--------------------------------------|---|
| Product identifier | Industrial Epoxy - Comp. A GREY |
| Other Means of Identification | PE700232 |
| Recommended Use | Epoxy Resin |
| Restrictions on Use | Unknown |
| Supplier Identifier | SCI Coatings Inc. 2821 Le Corbusier Laval Quebec Canada H7L 4J5 Web: www.SCICoatings.com |
| Emergency Phone No. | 24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666 |

| SECTION 2. HAZARD IDENTIFICATION | |
|----------------------------------|--|
| Classification | Skin Sensitization Category 1B Skin Corrosion/irritation Category 2 Serious eye damage/irritation Category 2A Acute Toxicity, Oral Category 5 Hazardous to the aquatic environment - acute Category 2 Hazardous to the aquatic environment - chronic Category 2 |

Label Elements



Signal Word

Warning

Hazard Statements

H303: May be harmful if swallowed
H315: Causes skin irritation
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H401: Toxic to aquatic life
H411: Toxic to aquatic life with long lasting effects

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash with plenty of water and soap thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/eye protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P312 IF SWALLOWED: Call a



Safety Data Sheet

POISON Center/doctor/...if you feel unwell. P362 + P364 Take off contaminated clothing and wash before reuse. P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

| Chemical Name | CAS No. | % Concentration |
|---|------------|-----------------|
| Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin | 25085-99-8 | 50 - 85 % |
| alkyl glycidyl ether | 68609-97-2 | 1 - 8 % |
| benzyl alcohol | 100-51-6 | 1 - 8 % |

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Ingestion:

IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

water jet

Specific Hazards Arising from the Product

During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

Special Protective Equipment and Precautions for Fire-fighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire-fighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.



SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

| Chemical Name | ACGIH® TLV® | | OSHA PEL | | AIHA® WEEL® | |
|---------------|-------------|----------|----------|---------|-------------|------------|
| | TWA | STEL [C] | TWA | Ceiling | 8-hr TWA | Short-term |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---------------|
| Appearance | Clear Liquid |
| Odor | Not available |
| Odor threshold | Not available |
| pH | Not available |
| Melting Point | Not available |
| Initial Boiling Point / Range | Not Available |
| Flash point | >93 |
| Evaporation rate | Not available |
| Flammability (solid; gas) | Not available |
| Lower flammable/explosive limit | Not available |
| Upper flammable/explosive limit | Not available |
| Vapor pressure | Not available |
| Vapor density | Not available |
| Specific gravity | 1.19 |
| Solubility | Partial |
| Partition coefficient – n- Octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | Not available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | Non-reactive |
| Chemical stability | Stable under recommended handling and storage conditions |
| Possibility of Hazardous reactions | This product will polymerize if mixed with an amine. Considerable heat can evolve. |
| Conditions to avoid | Avoid temperatures exceeding the |



Safety Data Sheet

| | |
|---|---|
| | flash point. Avoid unintended contact with amines. |
| Incompatible materials | Strong oxidizers, strong alkalis, strong mineral acids, amines. |
| Hazardous decomposition products | Unknown |

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/ Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation

No data

Aspiration Hazard

Not classified based on available data.

STOT (Specific Target Organ Toxicity) – Repeated Exposure

No data

Respiratory and/or Skin Sensitization

May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema. Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination

Carcinogenicity

Unknown

| Chemical Name | IARC | ACGIH® | NTP | OSHA |
|---------------|------|--------|-----|------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Hazardous to aquatic environment

This is not required by WHMIS



Safety Data Sheet

This is not required by OSHA HCS 2012

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorohydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorohydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorohydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

SECTION 15. REGULATORY INFORMATION

Not required under Canadian Regulations.

SECTION 16. OTHER INFORMATION


Date of Preparation August 2020

Date of Last Revision June 1, 2014

Revision Indicators The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.

References
1. CHOHS Fact Sheets September 2016 ©CCOHS 2016
2. Supplier's Material Safety Data Sheet(s)

| | |
|-------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ATE | Acute toxicity estimate |
| CAS | Chemical Abstract Service |
| DSL | Domestic Substance List |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods Code |
| LC | Lethal concentration |
| LD | Lethal Dosage |
| NIOSH | National Institute for Occupational Safety and Health |
| NTP | National Toxicology Program (U.S.A.) |
| OSHA | Occupational Safety and Health Administration (U.S.A.) |
| PEL | Permissible Exposure Limit |
| STEL | Short-term Exposure Limit |
| TDG | Transport of dangerous goods in Canada |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| TWA | Time Weighted Average |
| WHMIS | Workplace Hazardous Materials Information System |



Safety Data Sheet

Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that SCI Coatings Inc will not be liable for any damages resulting from its use since SCI Coatings Inc cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

| SECTION 1. IDENTIFICATION | |
|--------------------------------------|--|
| Product identifier | Industrial Epoxy - Comp. B |
| Other Means of Identification | PE700231 • PE700232 |
| Recommended Use | Epoxy hardener |
| Restrictions on Use | Unknown |
| Supplier Identifier | SCI COATINGS INC. 2821 Boul. Le Corbusier Laval, Quebec Canada H7L 4J5 Web: www.sealchem.com |
| Emergency Phone No. | 24-Hour Emergency Telephone Number Canada (CANUTEC) : (613) 996-6666 |

| SECTION 2. HAZARD IDENTIFICATION | |
|----------------------------------|--|
| Classification | Acute Toxicity, Oral Category 4 Skin Sensitization Category 1A Skin Corrosion/irritation Category 1B Serious eye damage/irritation Category 1 Reproductive toxicity Category 2 Hazardous to the aquatic environment - acute Category 1 Hazardous to the aquatic environment - chronic Category 1 |

Label Elements



Signal Word

Danger

Hazard Statements

- H302: Harmful if swallowed
- H317: May cause an allergic skin reaction
- H314: Causes severe skin burns and eye damage
- H318: Causes serious eye damage
- H361: Suspected of damaging fertility or the unborn child
- H400: Very toxic to aquatic life
- H410: Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention:

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust or mist. P280 Wear protective gloves/protective clothing/eye protection/face protection. P272 Contaminated work clothing should not be allowed out of the workplace. P270 Do not eat, drink or smoke when using this product. P264 Wash with plenty of water and soap thoroughly after handling. P308 + P313 IF exposed or concerned: Get medical advice/attention.

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [shower]. P310 Immediately call a POISON CENTER or doctor/physician. P363 Wash contaminated clothing before reuse. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P312 Call a POISON CENTER/doctor if you feel unwell. P362 + P364 Take off contaminated clothing and wash before reuse. P273 Avoid release to the environment. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

| SECTION 3. COMPOSITION | | |
|--------------------------------------|------------|-----------------|
| Chemical Name | CAS No. | % concentration |
| Bis phenol A / Epichlorohydrin resin | 25085-99-8 | 1 - 10 % |
| isophorone diamine | 2855-13-2 | 20 - 30 % |
| benzyl alcohol | 100-51-6 | 1 - 10 % |
| 4-nonylphenol, branched | 84852-15-3 | 20 - 40 % |
| polyoxypropylene diamine | 9046-10-0 | 20 - 40 % |

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

F INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

water jet

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Special Protective Equipment and Precautions for Fire-fighters

Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well-ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

| | | |
|-------------|----------|-------------|
| ACGIH® TLV® | OSHA PEL | AIHA® WEEL® |
|-------------|----------|-------------|

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

| Chemical Name | TWA | STEL [C] | TWA | Ceiling | 8-hr TWA | Short-term |
|---------------|-----|----------|-----|---------|----------|------------|
| | | | | | | |
| | | | | | | |
| | | | | | | |

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

| SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES | |
|---|---------------|
| Appearance | Clear Liquid |
| Odor | Not available |
| Odor threshold | Not available |
| pH | Not available |
| Melting Point | Not available |
| Initial Boiling Point / Range | Not available |
| Flash point | >93 |
| Evaporation rate | Not available |
| Flammability(solid; gas) | Not available |
| Lower flammable/explosive limit | Not available |
| Upper flammable/explosive limit | Not available |
| Vapor pressure | Not available |
| Vapor density | Not available |
| Specific gravity | 0.986 |
| Solubility | Partial |

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

| | |
|---|---------------|
| Partition coefficient – n- Octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |

| SECTION 10. STABILITY AND REACTIVITY | |
|---|---|
| Reactivity | Non-reactive |
| Chemical stability | Stable under recommended handling and storage conditions |
| Possibility of Hazardous reactions | This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions. |
| Incompatible materials | Strong oxidizing agents and acids. |
| Hazardous decomposition products | Unknown |

| SECTION 11. TOXICOLOGY INFORMATION | | | | |
|--|------|--------|-----|------|
| Likely Routes of Administration | | | | |
| Inhalation, skin contact, eye contact, ingestion. | | | | |
| Acute Toxicity | | | | |
| Oral: Harmful if swallowed. | | | | |
| Dermal: Harmful in contact with skin. | | | | |
| LD50 and LC50 Data | | | | |
| Not available | | | | |
| Skin Corrosion/Irritation | | | | |
| Causes skin irritation. | | | | |
| Serious Eye Damage/ Irritation | | | | |
| Causes serious eye damage | | | | |
| STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation | | | | |
| May cause allergy or asthma symptoms or breathing difficulties if inhaled. | | | | |
| Aspiration Hazard | | | | |
| Not classified based on available data. | | | | |
| STOT(Specific Target Organ Toxicity) – Repeated Exposure | | | | |
| Skin, eyes, central nervous system, respiratory system | | | | |
| Respiratory and/or Skin Sensitization | | | | |
| No data | | | | |
| Carcinogenicity | | | | |
| Unknown | | | | |
| Chemical Name | IARC | ACGIH® | NTP | OSHA |
| | | | | |
| | | | | |
| | | | | |

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Toxic to aquatic life with lasting effects.

This is not required by WHMIS

This is not required by OSHA HCS 2012

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT

SECTION 15. REGULATORY INFORMATION

Not required under Canadian Regulations.

SECTION 16. OTHER INFORMATION

Date of Preparation August 2020

Date of Last Revision June 1, 2014

Revision Indicators The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.

References
 1. CHOHS Fact Sheets September 2016 ©CCOHS 2016
 2. Supplier's Material Safety Data Sheet(s)

| | |
|--------------|--|
| ACGIH ATE | American Conference of Governmental Industrial Hygienists Acute toxicity estimate |
|--------------|--|

SAFETY DATA SHEET (SDS)

Industrial Epoxy - Comp. B
 PE700231 • PE700232

Date and version: November 14, 2022, Version 1

| | |
|-------|--|
| CAS | Chemical Abstract Service |
| DSL | Domestic Substance List |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods Code |
| LC | Lethal concentration |
| LD | Lethal Dosage |
| NIOSH | National Institute for Occupational Safety and Health |
| NTP | National Toxicology Program (U.S.A.) |
| OSHA | Occupational Safety and Health Administration (U.S.A.) |
| PEL | Permissible Exposure Limit |
| STEL | Short-term Exposure Limit |
| TDG | Transport of dangerous goods in Canada |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| TWA | Time Weighted Average |
| WHMIS | Workplace Hazardous Materials Information System |

Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that SCI Coatings Inc will not be liable for any damages resulting from its use since SCI Coatings Inc cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.