

# High solid Self levelling High Density Epoxy Coating - Part A PE700299

SECTION 1.	IDENTIFICATION		
	Product identifier	High solid Self levelling High Density Epoxy Coating - Part A PE700299	
	Other Means of Identification	N.A.	
	Recommended Use	Contaminated Floor Epoxy Coating	
	Recommended on Use	Unknown	
	Supplier Identifier	SCI COATINGS INC. 2821 Boulevard Le Corbusier Laval, Québec Canada H7L 4J5 www.scicoatings.com	
	Emergency Phone No.	24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666	

#### SECTION 2. HAZARD IDENTIFICATION

#### Classification

Skin Sensitization Category 1B

Skin Corrosion/irritation Category 2

Serious eye damage/irritation Category 2A

Acute Toxicity, Oral Category 5

Hazardous to the aquatic environment - acute Category 2
Hazardous to the aquatic environment - chronic Category 2

## **Label Elements**





## Signal Word

Warning

### **Hazard Statements**

H303	May be harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects



## High solid Self levelling High Density Epoxy Coating - Part A PE700299

#### **Precautionary statements**

#### Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash with plenty of water and soap thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/eye protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P312 IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

P362 + P364 Take off contaminated clothing and wash before reuse.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

#### SECTION 3. COMPOSITION

Chemical Name	CAS No.	% concentration
Reaction product: bisphenol-A-	25085-99-8	60-70%
(epichlorohydrin) epoxy resin		
Alkyl (C12-C14) glycidyl ether	68609-97-2	1-10%
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	5-10%
Bisphenol-F/epichlorohydrin epoxy resin	28064-14-4	5-10%
Benzyl Alcohol	100-51-6	1-10%

#### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

#### Ingestion:

IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

#### **Skin Contact:**

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

#### **Eye Contact:**

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

#### Most Important Symptoms and Effects, Acute and Delayed

#### If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

#### If in eyes:

Causes serious eye damage.

#### If ingested:

Ingestion is likely to be harmful or have adverse effects.

#### **Immediate Medical Attention and Special Treatment:**

#### Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SDS

PE700299 Part A April 09, 2024 Revision #1



## High solid Self levelling High Density Epoxy Coating - Part A PE700299

#### SECTION 5. FIRE-FIGHTING MEASURES

#### **Extinguishing Media**

#### **Suitable Extinguishing Media**

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

#### **Unsuitable Extinguishing Media**

Water jet

#### Specific Hazards Arising from the Product

During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

#### Special Protective Equipment and Precautions for Fire-fighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire- fighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment, and Emergency Procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

#### Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

### SECTION 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

#### **Conditions for Safe Storage**

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.



## High solid Self levelling High Density Epoxy Coating - Part A PE700299

#### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control Parameters**

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <a href="http://www.ccohs.ca/topics/hazards/chemical/chemicals/">http://www.ccohs.ca/topics/hazards/chemical/chemicals/</a>

#### **Appropriate Engineering Controls**

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

#### **Individual Protection Measures**









#### **General Measures**

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

#### Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

#### **Skin Protection**

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

#### **Respiratory Protection**

If insufficient ventilation, wear respiratory protection.



High solid Self levelling High Density Epoxy Coating - Part A PE700299

SECTION 9.	PHYSICAL AND CHEMICAL PROPERTIES	
	Appearence	Clear Liquid
	Odor	Not available
	Odor threshold	Not available
	рН	Not available
	Melting Point	Not available
	Initial Boiling Point / Range	Not available
	Flash point	>93°C
	Evaporation rate	Not available
	Flammability (solid; gas)	Not available
	Lower flammable/explosive limit	Not available
	Upper flammable/explosive limit	Not available
	Vapor pressure	Not available
	Vapor density	Not available
	Specific gravity	1.14
	Solubility	Partial
	Partition coefficient-n-Octanol/water	Not available
	Auto-ignition temperature	Not available
	Decomposition temperature	Not available
	Viscosity	Not available
SECTION 10.	STABILITY AND REACTIVITY	
	Reactivity	Non-reactive
	Chemical stability	Stable under recommended handling and storage conditions.
	Possibility of hazardous reactions	This product will polymerize if mixed with an epoxy resin.  Considerable heat can evolve.
	Conditions to avoid	Avoid temperatures exceeding the flash point. Avoid unintended contact with amines.
	Incompatible materials	Strong oxidizers, strong alkalis, strong mineral acids, amines.
	Hazardous decomposition products	Unknown



# High solid Self levelling High Density Epoxy Coating - Part A PE700299

ECTION 11.	TOXICOLOGY INFORMATION		
	Likely Routes of Administration	Inhalation, skin contact, eye contact, ingestion.	
	Acute Toxicity	Oral: Harmful if swallowed.	
	Acute Toxicity	Dermal: Harmful in contact with skin.	
	LD50 and LC50 Data	Not available	
	Skin Corrosion/Irritation	Causes skin irritation.	
	Serious Eye Damage/ Irritation	Causes serious eye damage.	
	STOT (Specific Target Organ Toxicity) Single Exposure Inhalation	No data	
	Aspiration Hazard	Not classified based on available data.	
	STOT(Specific Target Organ Toxicity) Repeated Exposure	No data	
	Respiratory and/or Skin Sensitization	May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema.  Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination.	
	Carcinogenicity	Unknowm	
	Reproductive Toxicity	Not available	
	Germ Cell Mutagenicity	Not available	
	Interactive Effects	Not available	
ECTION 12.	ECOLOGICAL INFORMATION  Hazardous to aquatic environment This is not required by WHMIS This is not required by OSHA HCS 2012		
ECTION 13.	DISPOSAL CONSIDERATIONS  Disposal Methods Dispose of contents/container into safe container in accordance with local, regional or national regulations.		
ECTION 14.	TRANSPORT INFORMATION  UN Number; Proper shipping name; Class(es); Packing UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTA	group (PG) of the TDG Regulations:  NCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; F	
	UN Number; Proper shipping name; Class(es); Packing UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTA	group (PG) of the IMDG (maritime): NCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; F	

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG

III; MARINE POLLUTANT

III; MARINE POLLUTANT

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):



# High solid Self levelling High Density Epoxy Coating - Part A PE700299

SECTION 15.	REGULATORY INFORMATION		
	Not required under Canadian	Regulations.	
SECTION 16.	OTHER INFORMATION		
	Date of Preparation	August 2022	
	Date of Last Revision	April 09, 2024	
	Revision Indicators	The entire MDSD was changed in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.	
	References	CHOHS Fact Sheets September 2016 ©CCOHS 2016     Supplier's Material Safety Data Sheet(s)	
	ACGIH	American Conference of Governmental Industrial Hygienists	
	ATE	Acute toxicity estimate	
	CAS	Chemical Abstract Service	
	DSL	Domestic Substance List	
	IARC	International Agency for Research on Cancer	
	IATA	International Air Transport Association	
	IMDG	International Maritime Dangerous Goods Code	
	LC	Lethal concentration	
	LD	Lethal Dosage	
	NIOSH	National Institute for Occupational Safety and Health	
	NTP	National Toxicology Program (U.S.A.)	
	OSHA	Occupational Safety and Health Administration (U.S.A.)	
	PEL	Permissible Exposure Limit	
	STEL	Short-term Exposure Limit	
	TDG	Transport of dangerous goods in Canada	
	TLV	Threshold Limit Value	
	TSCA	Toxic Substances Control Act	
	TWA	Time Weighted Average	
	WHMIS	Workplace Hazardous Materials Information System	

**NOTICE:** The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Passeport Élite will not be liable for any damages resulting from its use since Passeport Élite cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.