

High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 1.	IDENTIFICATION			
	Product identifier	High solid Self levelling High Density Epoxy Coating - Part B PE700299		
	Other Means of Identification	N.A.		
	Recommended Use	Contaminated floor epoxy repair		
	Recommended on Use	Unknown		
	Supplier Identifier	SCI COATINGS INC. 2821 Boulevard Le Corbusier Laval, Québec Canada H7L 4J5 www.scicoatings.com		
	Emergency Phone No.	24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666		

SECTION 2. HAZARD IDENTIFICATION

Classification

Acute Toxicity, Oral (Category 4)

Acute Toxicity, Dermal (Category 4)

Skin Sensitization (Category 1)

Respiratory Sensitization (Category 1)

Skin Corrosion/irritation (Category 1B)

Serious eye damage/irritation (Category 1)

Reproductive toxicity, Additional category lactation

Reproductive toxicity, fertility (Category 2)

Reproductive toxicity, unborn child (Category 1B)

Specific target organ toxicity - single exposure (Category 3 irritating to respiratory system)

Hazardous to the aquatic environment - acute (Category 1)

Hazardous to the aquatic environment - chronic (Category 1)

Label Elements









Signal Word

Danger

Hazard Statements

H302	Harmful if swallowed
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H314	Causes severe skin burns and eye damage
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H360	May cause harm to breast-fed children
H361	May damage the unborn child. Suspected of damaging fertility
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

PASSEPORT

Safety Data Sheet (SDS)

High solid Self levelling High Density Epoxy Coating - Part B PE700299

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.

P263 Avoid contact during pregnancy/while nursing.

P264 Wash with plenty of water and soap thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P305 + P351+ P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P341 + P311 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P362 + P364 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use water spray, dry powder, or foam for extinction.

P233 Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

GHS Special labeling: EUH205 - "Contains epoxy constituents. May produce a skin allergy."

SECTION 3.	COMPOSITION			
	Chemical Name	CAS No.	% concentration	
	Isophorone diamine	2855-13-2	15 - 25 %	
	Benzyl alcohol	100-51-6	1 - 10 %	
	4-nonylphenol, branched	84852-15-3	10 - 20 %	
	Polyoxypropylene diamine	9046-10-0	15 - 25 %	
	Amine curing agent	Mixture	13 - 20 %	



High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eve Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

Burning pain and severe corrosive skin damage. Can burn mouth, throat, and stomach. Can cause severe irritation and burns to the respiratory tract. May cause an allergic respiratory reaction. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Immediate Medical Attention and Special Treatment:

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

Water jet

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Special Protective Equipment and Precautions for Fire-fighters

Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.



High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapors of the product should be ventilated and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to wellventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under http://www.ccohs.ca/topics/hazards/chemical/chemicals/

	ACGIH ®	TLV®	OSHA	PEL	AIHA®	WEEL®
Chemical Name	TWA	STEL®	TWA	Ceiling	8-hr TWA	Short-Term

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures









General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.



High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 9.	PHYSICAL AND CHEMICAL PROPERTIES			
	Appearence	Clear Liquid		
	Odor	Not available		
	Odor threshold	Not available		
	рН	Not available		
	Melting Point	Not available		
	Initial Boiling Point / Range	Not available		
	Flash point	93°C		
	Evaporation rate	Not available		
	Flammability (solid; gas)	Not available		
	Lower flammable/explosive limit	Not available		
	Upper flammable/explosive limit	Not available		
	Vapor pressure	Not available		
	Vapor density	Not available		
	Specific gravity	1.05		
	Solubility	Partial		
	Partition coefficient-n-Octanol/water	Not available		
	Auto-ignition temperature	Not available		
	Decomposition temperature	Not available		
SECTION 10.	STABILITY AND REACTIVITY			
	Reactivity	Non-reactive		
	Chemical stability	Stable under recommended handling and storage conditions.		
	Possibility of hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.		
	Conditions to avoid	Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions.		
	Incompatible materials	Strong oxidizing agents and acids.		
	Hazardous decomposition products	Unknown		



High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 11.	TOXICOLOGY INFORMATION			
	Likely Routes of Administration	Inhalation, skin contact, eye contact, ingestion.		
	Acute Toxicity	Oral: Phenol LD50: 317 mg/kg (rat) Dermal: Harmful in contact with skin LD50: 850 mg/kg		
	LD50 and LC50 Data	Not available		
	Skin Corrosion/Irritation	Causes skin irritation.		
	Serious Eye Damage/ Irritation	Causes serious eye damage.		
	STOT (Specific Target Organ Toxicity) Single Exposure Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
	Aspiration Hazard	Not classified based on available data.		
	STOT(Specific Target Organ Toxicity) Repeated Exposure	Skin, eyes, central nervous system, respiratory system.		
	Respiratory and/or Skin Sensitization	No data		
	Carcinogenicity	Unknowm		
	Chemical name	IARC ACGIH® NTP OSHA		
	Reproductive Toxicity	Not available		
	Germ Cell Mutagenicity	Not available		
	Interactive Effects	Not available		
SECTION 12.	Toxic to aquatic life with lasting effects. This is not required by WHMIS. This is not required by OSHA HCS 2012.			
SECTION 13.	DISPOSAL CONSIDERATIONS Disposal Methods Dispose of contents/container into safe container in a	accordance with local, regional or national regulations.		
SECTION 14.	UN Number; Proper shipping name; Class(es); Packing gro UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. POLLUTANT UN Number; Proper shipping name; Class(es); Packing gro	. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III bup (PG) of the IMDG (maritime): . (. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE bup (PG) of the IATA (air):		
SECTION 15.	UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. POLLUTANT REGULATORY INFORMATION Not required under Canadian Regulations.	. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE		



High solid Self levelling High Density Epoxy Coating - Part B PE700299

SECTION 16.	OTHER INFORMATION	
	Date of Preparation	August 2022
	Date of Last Revision	April 09, 2024
	Revision Indicators	The entire MDSD was changed in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
	References	CHOHS Fact Sheets September 2016 ©CCOHS 2016 Supplier's Material Safety Data Sheet(s)
	ACGIH	American Conference of Governmental Industrial Hygienists
	ATE	Acute toxicity estimate
	CAS	Chemical Abstract Service
	DSL	Domestic Substance List
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods Code
	LC	Lethal concentration
	LD	Lethal Dosage
	NIOSH	National Institute for Occupational Safety and Health
	NTP	National Toxicology Program (U.S.A.)
	OSHA	Occupational Safety and Health Administration (U.S.A.)
	PEL	Permissible Exposure Limit
	STEL	Short-term Exposure Limit
	TDG	Transport of dangerous goods in Canada
	TLV	Threshold Limit Value
	TSCA	Toxic Substances Control Act
	TWA	Time Weighted Average
	WHMIS	Workplace Hazardous Materials Information System

<u>NOTICE:</u> The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Passeport Élite will not be liable for any damages resulting from its use since Passeport Élite cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.