


**SECTION 1. IDENTIFICATION**

<b>Product identifier</b>	Clear Passeport Elite Floor Epoxy - Part A PE700910
<b>Other Means of Identification</b>	N.A.
<b>Recommended Use</b>	Epoxy coating
<b>Recommended on Use</b>	Unknown
<b>Supplier Identifier</b>	SCI COATINGS INC. 8320 Rue Grenache, Anjou, Québec Canada H1J 1C5 www.scicoatings.com
<b>Emergency Phone No.</b>	<b>24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666</b>

**SECTION 2. HAZARD IDENTIFICATION**

<b>Classification</b>	
Skin Sensitization Category 1B Skin Corrosion/irritation Category 2 Serious eye damage/irritation Category 2A Acute Toxicity, Oral Category 5 Hazardous to the aquatic environment - acute Category 2 Hazardous to the aquatic environment - chronic Category 2	
<b>Label Elements</b>	
	
<b>Signal Word</b>	
Warning	
<b>Hazard Statements</b>	
H303	May be harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

**Precautionary statements**

**Prevention:**

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash with plenty of water and soap thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/eye protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P312 IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.
- P362 + P364 Take off contaminated clothing and wash before reuse.
- P273 Avoid release to the environment.
- P391 Collect spillage.
- P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

**Other Hazards:** Unknown

**SECTION 3. COMPOSITION**

Chemical Name	CAS No.	% concentration
Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin	25085-99-8	50-80%
Alkyl (C12-C14) glycidyl ether	68609-97-2	1-10%
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	17557-23-2	5-10%
Bisphenol-F/epichlorohydrin epoxy resin	28064-14-4	5-10%
Benzyl Alcohol	100-51-6	1-10%

**SECTION 4. FIRST-AID MEASURES**

**First-aid Measures**  
**Ingestion:**  
IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.  
**Skin Contact:**  
Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.  
**Eye Contact:**  
Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

**Most Important Symptoms and Effects, Acute and Delayed**  
**If inhaled:**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
**If on skin:**  
Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction.  
**If in eyes:**  
Causes serious eye damage.  
**If ingested:**  
Ingestion is likely to be harmful or have adverse effects.

**Immediate Medical Attention and Special Treatment:**  
**Special Instructions:**  
If a physician or medical attention is required, have product container or label at hand.

**SECTION 5. FIRE-FIGHTING MEASURES**

**Extinguishing Media**  
**Suitable Extinguishing Media**  
In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO<sup>2</sup>)  
**Unsuitable Extinguishing Media**  
Water jet

**Specific Hazards Arising from the Product**  
During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

**Special Protective Equipment and Precautions for Fire-fighters**  
Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire- fighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment, and Emergency Procedures**  
Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

**Methods and Materials for Containment and Clean up**  
For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

**SECTION 7. HANDLING AND STORAGE**

**Precautions for Safe Handling**  
 Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for Safe Storage**  
 Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control Parameters**  
 All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation. Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>.

**Appropriate Engineering Controls**  
 Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

**Individual Protection Measures**

**General Measures**  
 Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

**Eye / Face Protection**  
 Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

**Skin Protection**  
 Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

**Respiratory Protection**  
 If insufficient ventilation, wear respiratory protection.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Clear Liquid
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not available
Flash point	>93°C
Evaporation rate	Not available
Flammability (solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.14
Solubility	Partial
Partition coefficient-n-Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the flash point. Avoid unintended contact with amines.
Incompatible materials	Strong oxidizers, strong alkalis, strong mineral acids, amines.
Hazardous decomposition products	Unknown

**SECTION 11. TOXICOLOGY INFORMATION**

Likely Routes of Administration	Inhalation, skin contact, eye contact, ingestion.
Acute Toxicity	Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.
LD50 and LC50 Data	Not available
Skin Corrosion/Irritation	Causes skin irritation.
Serious Eye Damage/ Irritation	Causes serious eye damage.
STOT (Specific Target Organ Toxicity) Single Exposure Inhalation	No data
Aspiration Hazard	Not classified based on available data.
STOT(Specific Target Organ Toxicity) Repeated Exposure	No data

<b>Respiratory and/or Skin Sensitization</b>	May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema. Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination.
<b>Carcinogenicity</b>	Unknown
<b>Reproductive Toxicity</b>	Not available
<b>Germ Cell Mutagenicity</b>	Not available
<b>Interactive Effects</b>	Not available

**SECTION 12. ECOLOGICAL INFORMATION**

Hazardous to aquatic environment  
 This is not required by WHMIS  
 This is not required by OSHA HCS 2012

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal Methods**  
 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

**SECTION 14. TRANSPORT INFORMATION**

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:  
 UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):  
 UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):  
 UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

**SECTION 15. REGULATORY INFORMATION**

Not required under Canadian Regulations.



**Safety Data Sheet (SDS)**  
**Clear Passeport Elite Floor Epoxy - Part A**  
**PE700910**

**SECTION 16. OTHER INFORMATION**

<b>Date of Preparation</b>	August 2022
<b>Date of Last Revision</b>	January 4, 2023
<b>Revision Indicators</b>	The entire MSDS was changed in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
<b>References</b>	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s)
<b>ACGIH</b>	American Conference of Governmental Industrial Hygienists
<b>ATE</b>	Acute toxicity estimate
<b>CAS</b>	Chemical Abstract Service
<b>DSL</b>	Domestic Substance List
<b>IARC</b>	International Agency for Research on Cancer
<b>IATA</b>	International Air Transport Association
<b>IMDG</b>	International Maritime Dangerous Goods Code
<b>LC</b>	Lethal concentration
<b>LD</b>	Lethal Dosage
<b>NIOSH</b>	National Institute for Occupational Safety and Health
<b>NTP</b>	National Toxicology Program (U.S.A.)
<b>OSHA</b>	Occupational Safety and Health Administration (U.S.A.)
<b>PEL</b>	Permissible Exposure Limit
<b>STEL</b>	Short-term Exposure Limit
<b>TDG</b>	Transport of dangerous goods in Canada
<b>TLV</b>	Threshold Limit Value
<b>TSCA</b>	Toxic Substances Control Act
<b>TWA</b>	Time Weighted Average
<b>WHMIS</b>	Workplace Hazardous Materials Information System

**NOTICE:** The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Passeport Élite will not be liable for any damages resulting from its use since Passeport Élite cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.