



SHUR-STIK

Technical Data Sheet

SHUR-STIK LIGHTWEIGHT SPACKLING COMPOUND # 7678



Product Description

A lightweight, all-purpose wall-repair compound ideally suited for both interior and exterior applications. This product will not shrink, crack, sag or bowl-out. It may be used to patch cracks, crevices and nail holes in drywall, plaster or wood. It is also recommended for smoothing imperfections in wall surfaces prior to hanging wall-covering and filling cracks or holes in wood surfaces prior to painting.

Features and Benefits

- Ready-to-Use
- Unique dry indicator, pink when wet, white when dry.
- Easy to spread
- Will not shrink, crack, sag or bowl-out
- Repeated applications are usually not necessary
- No sanding necessary
- Accepts oil or latex base paints
- No bleed through

Application

PREPARATION:

Area to be repaired must be dry and free from dust, dirt, loose plaster, grease or wax on the surface and in the crevices.

APPLICATION:

Use Lightweight Spackling Compound 7678 as it comes from the container. Apply with a putty knife or broad knife with a blade wider than the area to be patched. Use a minimum of strokes when smoothing to avoid fast set up. Dip blade in water for final stroking for a smoother finish. Sand if needed only after the compound has been allowed to thoroughly dry. Prime the area with a latex primer before painting or hanging wall covering. Clean tools and hands with water. Keep container tightly closed when not in use.

Coverage

Not applicable as each hole, crack or fissure will differ in size and depth.

Cautions

Do not take internally. Close container after each use. Keep out of reach of children.

Physical Properties

Viscosity @ 25°C. – (ASTM D217).....	245-265 1/10mm
Non-volatile	50% by weight
Sag Control.....	Excellent
Cracking.....	None
Freeze/Thaw Stability.....	Excellent
Weight per Gallon US.....	4.5 lbs.
Slump Resistance (ASTM D-2202).....	0.05" Max
Shrinkage (1/4" Deep x 1" Wide).....	None
PH.....	10.5

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.