



Premium Masking Solutions

3415 Q1® Multiple Purpose Masking Tape

3415 Q1® Multi Purpose Indoor Masking Tape is a semi crepe paper masking tape with natural rubber based adhesive. This tape is designed for almost all indoor paint works, so it's not UV and water resistant. It sticks well to multiple and irregular surfaces such as walls, baseboards, trims, wood, metal.

3415 Q1® Multi Purpose Indoor Masking Tape assures a clean and easy removal within 7 days, without leaving any residue on the application surface or peeling of the substrate. It performs in overlapping the tape, with masking paper and masking film with excellent holding power.



Features & Benefits

- Natural rubber adhesive for superior hold and clean removal
- Ideal for indoor use on both smooth and irregular surfaces
- No bleed through
- 7 days clean removal
- Tears neatly off the roll for effortless application

Available Colour

Sun Yellow

Product Reference

Part#	Size	Pcs/ Case
PMT124	24mm x 50 m	36 rolls/ case
PMT136	36mm x 50 m	24 rolls/ case
PMT148	48mm x 50 m	20 rolls/ case

Technical Data Sheet

Characteristics	Metric	Imperial Units	Test method
Total Weight	90g/m ²	90g/m ²	ISO 536
Total Thickness	120 µm	4.7 mils	Internal
MD tensile strength	38 N/cm	21.7 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break	7%	7%	AFERA 5004/PSTC 131
Adhesion to steel plate	2.1N/cm	19.2 oz/in	AFERA 5001/PSTC 101
Service temperature	up to 60°C	up to 140° F	

Additional Information

Storage & Handling

Q1[®] Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1[®] Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1[®] Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1[®] Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1[®] would advise that there are many factors beyond Q1[®] control but within the users knowledge that can affect the use and performance of Q1[®] products. Q1[®] remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1[®] literature.